



AP 9999 SYNTEC SN 10W-40

API SN

SAE 10W-40

SYN-TECH FOUR-STROKE ENGINE OIL

DESCRIPTION

AP 9999 SYNTEC SN 10W-40 is formulated to effectively maintain engine cleanliness and maximizes performance by preventing the formation of sludge and deposits. This oil ensures reliable cold start performance.

APPLICATIONS

AP 9999 SYNTEC SN 10W-40 is the premier choice for a wide range of modern vehicles, including automobiles, passenger vehicles, buses, and light-duty trucks from leading global brands such as Honda, Toyota, Ford, BMW, Nissan, GM, and Volkswagen. It is suitable for both gasoline and diesel engines meeting EURO II, III, IV, and V emission standards.

STANDARDS

- API SN/CF
- ACEA A3/B4

BENEFITS

- Deliver comprehensive wear protection under extreme temperature conditions
- Prevents heat-induced oil degradation and gelling
- Exhibit outstanding sludge and deposit resistance for sustained engine cleanliness



TYPICAL SPECIFICATIONS

Properties	Method	Unit	Limit
Kinematic Viscosity @ 100°C	ASTM D445	cSt	12.5 ÷ 16.2
Viscosity Index	ASTM D2270	--	Min 140
Flash point	ASTM D92	°C	Min 200
Pour Point	ASTM D97	°C	Max -30
Water Content	ASTM D95	%tt	Max 0.05
Pentane Insolubles	ASTM D4055	%kl	Max 0.1
Foam Tendency (Seq II) @ 93.5°C	ASTM D892	ml/ml	Max 50/0
Ca, Mg, Zn Content	ASTM D4951	%kl	Min 0.2
Copper Strip Corrosion (100°C, 3h)	ASTM D130	--	Nhóm 1
Total Base Number (TBN)	ASTM D2896	mgKOH/g	Min 5.0
Appearance	Visual	--	Bright & Clear

* These characteristics are typical of current production. Whilst future production will to APSP's specification, variations in these characteristics may occur.

PACKAGING

4L 200L 1000L As required

ENVIRONMENT, HEALTH & SAFETY**▪ Health & Safety**

AP 9999 SYNTEC SN 10W-40 does not cause any significant health hazards when used as directed and in compliance with personal and industrial hygiene standards.

Avoid contacting skin frequently with the used oil. Use appropriate gloves if necessary. If on skin, rinse carefully with soaps and water.

▪ Environmental protection

Dispose used oil at appropriate collection point. Do not discharge into drains, onto the ground, or into water sources.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet (MSDS), which can be obtained from <http://www.apsaigonpetro.com>

STORAGE

Storage temperature: Below 45°C. Avoid direct sunlight.

Keep away from heat and sources of ignition. Avoid water contamination, do not mix with other oils without recommendations

ADDITIONAL INFORMATION**▪ Technical**

Detailed information is available on our website, <http://www.apsaigonpetro.com>, or you may contact us directly through our hotline 1900 0104.