



AP ATF D6

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

AP ATF D6 is a premium automatic transmission fluid with Durafilm Technology designed for modern automatic transmissions. This advanced technology extends transmission life through a durable oil film, providing a smooth driving experience for an extended period.

APPLICATIONS

AP ATF D6 is recommended for automatic transmissions in passenger vehicles and heavy-duty trucks, power steering systems and certain hydraulic applications requiring ISO VG 32-46-68 viscosity grades.



STANDARDS

- JASO M315 Type 1A-LV
- Honda ATF DW-1, Z1
- GM W16444, DEXRON-VI
- Ford P/N XT-10-QLV
- MERCON LV
- Chrysler Type 9602
- Chrysler NAG2
- ZF TE-ML 11
- Toyota T-III, T-IV ASD
- Mazda ATF M-III, M-V, ZF
- Nissan Matic D, J, S
- Suzuki AT Oil 5D06, 2384K
- Subaru F6, Red 1
- AMMIX ATF D-III Multi, D3-SP
- Hyundai/Kia SP III, SP IV
- Suitable for 6-speed automatic

transmissions in Audi, BMW, Mini-Cooper, Jaguar, Peugeot/Citroen, Saab, Volvo, Porsche, and all vehicles requiring DEXRON III or Mercon SP type fluids

BENEFITS

• Friction modifier

Enhances the smoothness and dependability of automotive drivetrain operation, contributing to a comfortable driving feel.

• Excellent oxidation resistance

Prevents oil sludge formation caused by heat, maintaining a durable lubricant film.

• High viscosity index

Optimizes performance and minimizes power loss over a wide temperature range.

• Superior anti-wear properties

Specially formulated additives offer excellent wear protection for extended transmission life.

TYPICAL SPECIFICATIONS

Properties	Method	Unit	Limit
Kinematic viscosity @100°C	ASTM D445	cSt	6.5 ÷ 6.9
Viscosity index	ASTM D2270	-	Min 150
Flash point (open cup)	ASTM D92	°C	Min 200
Pour point	ASTM D97	°C	Max -30
Water content	ASTM D95	%tt	Max 0.05
Density @15°C	ASTM D4052		0.83 – 0.85
Appearance	Visual	-	Bright & Color

* These characteristics are typical of current production. Whilst future production will to APSP's specification, variations in these characteristics may occur.

PACKAGING


4L 200L 1000L As required

STORAGE

Storage temperature: Below 45°C. Avoid direct sunlight.

Keep away from heat and sources of ignition. Avoid water contamination, do not mix with other oils without recommendations.

ENVIRONMENT, HEALTH & SAFETY
▪ Health & Safety

AP ATF D6 does not cause any significant health hazards when used as directed and in compliance with personal and industrial hygiene standards.

Avoid contacting skin frequently with the used oil. Use appropriate gloves if necessary. If on skin, rinse carefully with soaps and water.

▪ Environmental protection

Dispose used oil at appropriate collection point. Do not discharge into drains, onto the ground, or into water sources.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet (MSDS), which can be obtained from <http://www.apsaigonpetro.com>.

ADDITIONAL INFORMATION
▪ Technical assistance

Detailed information is available on our website, <http://www.apsaigonpetro.com>, or you may contact us directly through our hotline 1900 0104.